

Product Specification		
General Information	Panel Brand	Samsung/LG/AUTO/ LCD/LED/Chimee
	Panel Size	42, 47, 55, 65 Inch Optional
	Product Color	Black,White,color of outershell is customized
IR Touch Screen Details	Touch Max Resolution	4096×4096
	Transparency	> 90%, Up to 100%
	Response Speed	<10ms
	Anti-Sunlight/ strong light interference	
	Touch Point	2 & 6 POINTS optional
PC Info	Minimum identification point	3mm x 3mm
	CPU	Intel i3 (i5,i7optional)
	RAM	4GB ,DDR3-1333, 8GB is optional
	Hard Disk	500GB
	Graphics	Intel HD4000
	WIFI	802.11 B.G.N
	Audio card	Realtek ALC662
	Camera	Optional
Interfaces	OS	DOS, WINDOWS 7 or UP/ME/2000/XP/2003/VISTA, LINUX.
	VGA Output	1
	HDMI Output	1
	Audio Output	1
	Microphone Input	1
	USB	4 or more depending on the main board
Accessory	RJ45	1
	Power supply cable, user manual, keys, adapter	
Temperature	Touch screen working temperature	-41° C ~70° C
	screen Storage Temperature	-50° C ~85° C
	The machine operating temperature	-4~65° C
	mahcine Storage Temperature	-7~65° C
Features	1.Build-in High Quality speakers Stereo 2pcs x 5W.	
	2.Build-in Mini-PC; It is optional for i3/i5/i7 .	
	3.Adopts IR multipoint Touch Screen.	
	4.Application fields:public places ,for example,shopping mall, restaurant,airport, square,commercial buidings,etc.	
	5.Combined hardware and software solution for fast, reliable delivery of digital signage content	
	6.Easy WIFI network system installation without the need for extra IT, firewall or security configurations.	